
Date of release: 10.10.2024; **Revision n°:** 3 **date:** 10.10.2024; **Approval:** R&D; **Verified:** QMS

1. Description

MC329 Fuel Water Remover is developed to absorb and remove (condensation) water from both petrol and diesel fuel tanks. Prevents fuel system corrosion and stops or reduces white smoke.

Benefits:

- ✓ Absorbs and removes water from both petrol and diesel fuel tanks
- ✓ Stops or reduces white smoke emission
- ✓ Protects against rust and corrosion
- ✓ Prevents fuel filter (and carburettor) icing
- ✓ Provides a better cold start performance
- ✓ Prevents bacterial growth

2. Technical Specification

Density g/cm ³	0,810
Color	Light blue / transparent
Odour	Characteristic
Flash point	22°C
Storage	Protect from sunlight
Expiry	5 years from production date

3. Use

Usage:

Recommended for all petrol and diesel engines with or without turbocharger. Will not harm catalytic converters.

Direction:

Pour the contents of one bottle in the fuel tank before filling it to the maximum level.

Dosage:

One bottle treats 40-60 litres of fuel.
For best results, use every six months.

Read and observe the safety warnings on the container label.

For information on handling, transport, etc., refer to the Safety Data Sheet for the product in question.

The information contained in this documentation refers to the knowledge of the product at the compilation date indicated above. However, considering the many possible uses and possible interferences from elements not dependent on the manufacturer, it is not possible to assume any responsibility regarding the indications.

ONZCA INDUSTRIAL [HTTP://www.onzca.com](http://www.onzca.com) – EMAIL: info@onzca.com