
Date of release: 10.10.2024; **Revision n°:** 3 **date:** 10.10.2024; **Approval:** R&D; **Verified:** QMS

1. Description

MC350 Cooling System Flush is especially developed to effectively and thoroughly clean the entire cooling system and to improve the heat transfer from the engine to the coolant / cooling system.

Benefits:

- ✓ Removes sludge, rust, scale and other deposits from the cooling system
- ✓ Improves heat transfer and prevents overheating
- ✓ Enables the fresh coolant to perform optimally
- ✓ Prevents build-up of acids and contaminants
- ✓ Does not contain acids and is not poisonous
- ✓ Does not harm rubber hoses, metal parts and gaskets

2. Technical Specification

Density g/cm³	1,00
Color	Clear
Odour	Neutral
pH	9,5 – 10,5
Storage	Protect from sunlight
Expiry	5 years from production date

3. Use

Suitable for all aluminium, plastic and steel radiators of cooling systems in petrol, diesel and LPG engines. Compatible with all cooling fluids, conventional antifreeze and water.

Direction:

Shake well before use. Add contents of one bottle to the radiator, drive for about 30 minutes and drain cooling system. Flush with water and refill cooling system with recommended coolant.

Important: be careful when opening the radiator or cooling system: hot coolant or steam might escape from the system!

Dosage:

One 300 ml bottle is sufficient for cooling systems with a volume of up to 12 litres.

Read and observe the safety warnings on the container label.

For information on handling, transport, etc., refer to the Safety Data Sheet for the product in question.

The information contained in this documentation refers to the knowledge of the product at the compilation date indicated above. However, considering the many possible uses and possible interferences from elements not dependent on the manufacturer, it is not possible to assume any responsibility regarding the indications.

ONZCA INDUSTRIAL [HTTP://www.onzca.com](http://www.onzca.com) – EMAIL: info@onzca.com